




Product Specification

Specification:

Item	Unit	Spec. Value	
Conductor	Wire No.	4P	
	Material	Solid Bare Copper	
	Construction	No./mm	0.45±0.01
Insulation	Material	PE	
	Diameter	mm	0.83±0.05
	Color	---	1.Blue&White Blue 2.Orange&White Orange 3.Green&White Green 4.Brown&White Brown
Rip cord	/	Yes	
Jacket	Material	PVC	
	Color	Assorted upon request	
	Thickness	mm	0.5±0.1
	Diameter	mm	4.7±0.3

Sketch:



Application:

1: Material : Comply RoHS

Mechanical Specification :

Conductor Elongation	≥10%
Insulation Tensile Strength	≥16.5Mpa
Insulation Elongation	≥300%
Jacket Tensile Strength	≥13.8Mpa
Jacket Elongation	≥100%

U/UTP CAT3 4P PVC



LAN cable

Electrical Specifications:

Impedance	100±15Ω (1.0-100Mhz)
Conductor Resistance @20 ° C	Max.11.7Ω/100m
DC Resistance Unbalance	Max.5%
Insulation Resistance	Min. 5000 MΩ*Km
Delay Skew	Max.45ns/100m

High Frequency Electrical Performance: :(at 20 °C 100m)

Frequency (MHz)	Insertion Loss (≤dB)	NEXT (≥dB)	PSNEXT (≥dB)	ACR-F (≥dB)	PS ACR-F (≥ dB)	RL (≥dB)	Spread out 100m cable and test it
1.00	3.0	60.0	57.0	57.4	54.4	17.0	
4.00	4.5	53.5	50.5	45.4	42.4	17.0	
8.00	6.3	48.6	45.6	39.3	36.3	17.0	
10.00	7.1	47.0	44.0	37.4	34.4	17.0	
16.00	9.1	43.6	40.6	33.3	30.3	17.0	
20.00	10.2	42.0	39.0	31.4	28.4	17.0	
25.00	11.4	40.3	37.3	29.4	26.4	16.0	
31.25	12.9	38.7	35.7	27.5	24.5	15.1	
62.50	18.6	33.6	30.6	21.5	18.5	12.1	
100.00	24	30.1	27.1	17.4	14.4	10.0	